



DIN 2215, ISO 4184

Objednávací číslo / Part.No.

10 x 610Li/632Lw ZX24

10 ... Profil / profile

610Li ... Vnitřní délka / Inside length



ZX/10

$b_0 = 10 \text{ mm}$

$h = 6 \text{ mm}$



Continental
CONTITECH

Typ CONTI-V® FO / ROFLEX RE-X - Profil ZX/10 - DIN2215

Typ řemenu / Part.No.				Typ řemenu / Part.No.				
Délka Li [mm]	Lw [mm]			Délka Li [mm]	Lw [mm]			
Length Li [mm]	Lw [mm]			Length Li [mm]	Lw [mm]			
ZX / 10				ZX / 10				
ZX 19	483	505	-	ZX 44	1118	1140	-	
ZX 19,5	495	517	-	ZX 45	1143	1165	-	
ZX 20	508	530	-	ZX 45,5	1156	1178	-	
ZX 20,5	521	543	-	ZX 46,5	1181	1203	-	
ZX 21	533	555	-	ZX 47,5	1207	1229	-	
ZX 21,7	551	573	-	ZX 49	1245	1267	-	
ZX 22,2	564	586	-	ZX 50	1270	1292	-	
ZX 23	584	606	-	ZX 50,7	1288	1310	-	
ZX 24	610	632	-	ZX 52	1321	1343	-	
ZX 24,7	627	649	-	ZX 53	1346	1368	-	
ZX 25,7	653	675	-	ZX 53,5	1359	1381	-	
ZX 26	660	682	-	ZX 54	1372	1394	-	
ZX 27	686	708	-	ZX 55	1397	1419	-	
ZX 28	711	733	-	ZX 55,7	1415	1437	-	
ZX 28,5	724	746	-	ZX 58	1473	1495	-	
ZX 29,5	749	771	-	ZX 59	1499	1521	-	
ZX 30	762	784	-	ZX 59,7	1516	1538	-	
ZX 30,5	775	797	-	ZX 60	1524	1546	-	
ZX 30,7	780	802	-	ZX 61	1549	1571	-	
ZX 31,5	800	822	-	ZX 62	1575	1597	-	
ZX 32	813	835	-	ZX 63	1600	1622	-	Lw max. ZX/10 = 5000 mm
ZX 32,5	834	856	-	ZX 64	1626	1648	-	
ZX 33	838	860	-	ZX 64,7	1643	1665	-	Li = Ld - 22 mm
ZX 33,7	856	878	-	ZX 66	1676	1698	-	La = Ld + 16 mm
ZX 35	889	911	-	ZX 67	1702	1724	-	La = Li + 38 mm
ZX 35,5	902	924	-	ZX 68	1727	1749	-	
ZX 36	914	936	-	ZX 70	1778	1800	-	Hmotnost řemenu / Belt weight = 0,060 kg/m
ZX 36,5	927	949	-	ZX 71	1803	1825	-	
ZX 37	940	962	-	ZX 73	1854	1876	-	Min. průměr řemenice 40mm
ZX 37,5	953	975	-	ZX 75	1905	1927	-	Min. pulley diameter 40mm
ZX 38	965	987	-	ZX 78	1981	2003	-	
ZX 39	991	1013	-	ZX 79	2007	2029	-	
ZX 39,5	1003	1025	-	ZX 80	2032	2054	-	Další nestandardní rozměry na požádání./
ZX 39,7	1008	1030	-	ZX 82	2083	2105	-	Other non-standard dimensions on demand.
ZX 40	1016	1038	-	ZX 85	2159	2181	-	
ZX 40,5	1029	1051	-	ZX 88	2235	2257	-	Lw = účinná délka / pitch length
ZX 41	1041	1063	-	ZX 90	2286	2308	-	Li = vnitřní délka / inside length
ZX 42	1067	1089	-	ZX 91	2311	2333	-	La = vnější délka / outside length
ZX 43	1092	1114	-					

!! Řemeny ZX/10 lze nahradit výkonnějšími řemeny XPZ/3VX / ZX/10 V-belts can be replaced by raw-edged XPZ/3VX !!