



DIN 2215, ISO 4184

Objednáací číslo / Part.No.

17 x 1372Li/1415Lw BX54

17 ... Profil / profile

1372Li ... Vnitřní délka / Inside length



BX/17

$b_0 = 17 \text{ mm}$

$h = 11 \text{ mm}$



Continental
CONTITECH

Typ CONTI-V® FO / ROFLEX RE-X - Profil BX/17 - DIN2215

Typ řemenu / Part.No.				Typ řemenu / Part.No.				Typ řemenu / Part.No.					
Délka Li [mm]		Lw [mm]		Délka Li [mm]		Lw [mm]		Délka Li [mm]		Lw [mm]			
Length Li [mm]		Lw [mm]		Length Li [mm]		Lw [mm]		Length Li [mm]		Lw [mm]			
BX / 17				BX / 17				BX / 17					
BX 23	584	627	-	BX 72	1829	1872	-	BX 124	3150	3193	-		
BX 26	660	703	-	BX 73	1854	1897	-	BX 125	3175	3218	-		
BX 27	686	729	-	BX 74	1880	1923	-	BX 126	3200	3243	-		
BX 28	710	754	-	BX 75	1900	1948	-	BX 127	3226	3269	-		
BX 29	737	780	-	BX 76	1930	1973	-	BX 128	3251	3294	-		
BX 30	762	805	-	BX 77	1956	1999	-	BX 130	3302	3345	-		
BX 31	787	830	-	BX 78	1981	2024	-	BX 132	3353	3396	-		
BX 32	813	856	-	BX 79	2007	2050	-	BX 133	3378	3421	-		
BX 33	838	881	-	BX 80	2032	2075	-	BX 134	3404	3447	-		
BX 34	864	907	-	BX 81	2057	2100	-	BX 135	3429	3472	-		
BX 35	889	932	-	BX 82	2083	2126	-	BX 136	3454	3497	-		
BX 36	914	957	-	BX 83	2108	2151	-	BX 138	3505	3548	-		
BX 36,7	932	975	-	BX 84	2134	2177	-	BX 140	3556	3599	-		
BX 37	940	983	-	BX 85	2159	2202	-	BX 146	3708	3751	-		
BX 38	965	1008	-	BX 86	2184	2227	-	BX 148	3759	3802	-		
BX 39	990	1034	-	BX 87	2210	2253	-	BX 150	3810	3853	-		
BX 40	1016	1059	-	BX 88	2235	2278	-	BX 152	3861	3904	-		
BX 41	1041	1084	-	BX 89	2261	2304	-	BX 154	3912	3955	-		
BX 42	1067	1110	-	BX 90	2286	2329	-	BX 157	3988	4031	-		
BX 43	1090	1135	-	BX 91	2311	2354	-	BX 158	4013	4056	-		
BX 44	1120	1161	-	BX 92	2337	2380	-	BX 162	4115	4158	-		
BX 45	1143	1186	-	BX 93	2360	2405	-	BX 163	4140	4183	-		
BX 46	1168	1211	-	BX 94	2388	2431	-	BX 165	4191	4234	-		
BX 47	1194	1237	-	BX 95	2413	2456	-	BX 168	4267	4310	-		
BX 48	1219	1262	-	BX 96	2438	2481	-	BX 173	4394	4437	-		
BX 49	1245	1288	-	BX 96,5	2451	2494	-	BX 175	4445	4488	-		
BX 50	1270	1313	-	BX 97	2464	2507	-	BX 180	4572	4615	-		
BX 51	1295	1338	-	BX 98	2489	2532	-	BX 185	4699	4742	-		
BX 52	1320	1364	-	BX 99	2515	2558	-	BX 187	4750	4793	-		
BX 53	1350	1389	-	BX 100	2540	2583	-	BX 188	4775	4818	-		
BX 54	1372	1415	-	BX 102	2591	2634	-	Lw max. BX/17 = 5000 mm Li = Ld - 43 mm La = Ld + 23 mm La = Li + 66 mm Hmotnost řemenu / Belt weight = 0,170 kg/m Min. průměr řemenice 90mm Min. pulley diameter 90mm Tučně označené rozměry jsou standardní. Bolt-typed belt sizes are standard. Lw = účinná délka / pitch length Li = vnitřní délka / inside length La = vnější délka / outside length					
BX 55	1400	1440	-	BX 103	2616	2659	-						
BX 56	1422	1465	-	BX 104	2642	2685	-						
BX 57	1450	1491	-	BX 105	2667	2710	-						
BX 58	1473	1516	-	BX 106	2692	2735	-						
BX 59	1500	1542	-	BX 107	2705	2748	-						
BX 60	1525	1567	-	BX 108	2743	2786	-						
BX 61	1550	1592	-	BX 110	2794	2837	-						
BX 62	1575	1618	-	BX 112	2845	2888	-						
BX 63	1600	1643	-	BX 112,5	2858	2901	-						
BX 64	1626	1669	-	BX 113	2870	2913	-						
BX 65	1651	1694	-	BX 114	2896	2939	-						
BX 66	1676	1719	-	BX 115	2921	2964	-						
BX 67	1700	1745	-	BX 116	2950	2993	-						
BX 68	1725	1770	-	BX 117	2972	3015	-						
BX 69	1750	1796	-	BX 118	2997	3040	-						
BX 70	1775	1821	-	BX 120	3048	3091	-						
BX 71	1800	1846	-	BX 122	3099	3142	-						

!! Řemeny BX/17 lze nahradit výkonnějšími řemeny XPB/5VX / BX/17 V-belts can be replaced by raw-edged XPB/5VX !!