



Figur 1F




Figur 2



Figur 2F



Figur 3F




Figur 5F

### Typ PC 14M - Pro řemeny PC GT Polychain 14M / For belts PC GT Polychain 14M


Zubů Teeth	Šíř.ř. Width	Označení / Obj.č. Part.No.	Typ Fig.	* Mat. Mat.	Pouzdro Bush	Max.díra Max.Bore	Dp [mm]	De [mm]	Df [mm]	Dm [mm]	Di [mm]	F [mm]	S [mm]	R [mm]	m [kg]
28	20	14M-28-S20	3F	GG	2012	50,0	124,78	121,98	141,0	-	-	33,0	32,0	1,0	2,46
	37	14M-28-S37	5F	GG	2012	50,0	124,78	121,98	141,0	-	88,0	51,0	32,0	19,0	2,97
30	20	14M-30-S20	3F	GG	2012	50,0	133,69	130,89	141,0	-	-	33,0	32,0	1,0	2,85
	37	14M-30-S27	6F	GG	2517	60,0	133,69	130,89	141,0	-	98,0	51,0	45,0	3,0	3,81
32	20	14M-32-S20	3F	GG	2012	50,0	142,60	139,80	155,0	-	-	33,0	32,0	1,0	3,26
	27	14M-32-S37	6F	GG	2517	60,0	142,60	139,80	155,0	-	100,0	51,0	45,0	3,0	4,53
34	20	14M-34-S20	2F	GG	2517	60,0	151,52	148,72	162,0	117,0	-	33,0	45,0	-	4,35
	37	14M-34-S37	6F	GG	2517	60,0	151,52	148,72	162,0	-	109,0	51,0	45,0	3,0	5,06
	68	14M-34-S68	1F	GG	PB40	100,0	151,52	148,72	162,0	134,0	-	84,0	104,0	-	6,25
36	20	14M-36-S20	2F	GG	2517	60,0	160,43	157,53	168,0	117,0	-	33,0	45,0	-	5,05
	37	14M-36-S37	5F	GG	2517	60,0	160,43	157,53	168,0	-	117,0	51,0	45,0	6,0	5,92
	68	14M-36-S68	1F	GG	PB40	110,0	160,43	157,53	168,0	134,0	-	84,0	104,0	-	6,68
	90	14M-36-S90	1F	GG	PB50	110,0	160,43	157,53	168,0	131,0	-	106,0	136,0	-	8,18
38	20	14M-38-S20	2F	GG	2517	60,0	169,34	166,54	183,0	117,0	-	33,0	45,0	-	5,39
	37	14M-38-S37	5F	GG	2517	60,0	169,34	166,54	183,0	-	126,0	51,0	45,0	6,0	6,51
	68	14M-38-S68	1F	GG	PB40	115,0	169,34	166,54	183,0	141,0	-	84,0	104,0	-	7,46
	90	14M-38-S90	1F	GG	PB50	115,0	169,34	166,54	183,0	147,0	-	106,0	136,0	-	9,73
	125	14M-38-S125	1F	GG	PB50	115,0	169,34	166,54	183,0	147,0	-	141,0	161,0	-	11,74
40	20	14M-40-S20	2F	GG	2517	60,0	178,25	175,45	197,0	117,0	-	33,0	45,0	-	5,97
	37	14M-40-S37	5F	GG	2517	60,0	178,25	175,45	197,0	-	135,0	51,0	45,0	6,0	7,31
	68	14M-40-S68	1F	GG	PB40	125,0	178,25	175,45	197,0	156,0	-	84,0	104,0	-	7,81
	90	14M-40-S90	1F	GG	PB50	125,0	178,25	175,45	197,0	156,0	-	106,0	136,0	-	10,29
	125	14M-40-S125	1F	GG	PB50	125,0	178,25	175,45	197,0	156,0	-	141,0	161,0	-	12,23
44	20	14M-44-S20	2F	GG	3020	75,0	196,08	193,28	211,0	144,0	-	33,0	51,0	-	8,03
	37	14M-44-S37	3F	GG	3020	75,0	196,08	193,28	211,0	-	-	51,0	51,0	-	9,44
	68	14M-44-S68	6F	GG	3020	75,0	196,08	193,28	211,0	-	153,0	84,0	51,0	16,5	11,54
	90	14M-44-S90	1F	GG	PB50	140,0	196,08	193,28	211,0	169,0	-	106,0	136,0	-	11,92
	125	14M-44-S125	1F	GG	PB50	140,0	196,08	193,28	211,0	170,0	-	141,0	161,0	-	14,46
48	20	14M-48-S20	2F	GG	3020	75,0	213,90	211,11	226,0	144,0	-	33,0	51,0	-	9,48
	37	14M-48-S37	3F	GG	3020	75,0	213,90	211,11	226,0	-	-	51,0	51,0	-	11,44
	68	14M-48-S68	5F	GG	3020	75,0	213,90	211,11	226,0	-	171,0	84,0	51,0	33,0	13,74
	90	14M-48-S90	6F	GG	3525	100,0	213,90	211,11	226,0	-	171,0	106,0	66,0	20,0	16,76
	125	14M-48-S125	1F	GG	PB50	160,0	213,90	211,11	226,0	185,0	-	141,0	161,0	-	14,70
50	20	14M-50-S20	2F	GG	3020	75,0	222,82	220,02	239,0	144,0	-	33,0	51,0	-	10,13
	37	14M-50-S37	3F	GG	3020	75,0	222,82	220,02	239,0	-	-	51,0	51,0	-	12,62
	68	14M-50-S68	6F	GG	3525	100,0	222,82	220,02	239,0	-	180,0	84,0	65,0	9,5	16,63
	90	14M-50-S68	6F	GG	3525	100,0	222,82	220,02	239,0	-	180,0	106,0	66,0	20,0	18,38
	125	14M-50-S125	6F	GG	3525	100,0	222,82	220,02	239,0	-	180,0	141,0	65,0	38,0	20,93
56	20	14M-56-S20	9F	GG	3020	75,0	249,55	246,76	267,0	144,0	207,0	33,0	51,0	9,0	10,81
	37	14M-56-S37	7F	GG	3020	75,0	249,55	246,76	267,0	144,0	207,0	51,0	51,0	0,0	12,70
	68	14M-56-S68	6F	GG	3525	100,0	249,55	246,76	267,0	-	207,0	84,0	65,0	9,5	21,15
	90	14M-56-S90	6F	GG	3525	100,0	249,55	246,76	267,0	-	207,0	106,0	66,0	20,0	23,46
	125	14M-56-S125	6F	GG	3525	100,0	249,55	246,76	267,0	-	207,0	141,0	65,0	38,0	25,91

\* Materiál: ST = ocel, GG = litina / ST = steel, GG = iron cast


PB.. = s předvrtanou dírou d=.. / PB = Min.plain bore




Figur 7




Figur 7F




Figur 8



Figur 9



Figur 9F



Figur 10

### Typ PC 14M - Pro řemeny PC GT Polychain 14M / For belts PC GT Polychain 14M

Zubů Teeth	Šíř.ř. Width	Označení / Obj.č. Part.No.	Typ Fig.	* Mat. Mat.	Pouzdro Bush	Max.díra Max.Bore	Dp [mm]	De [mm]	Df [mm]	Dm [mm]	Di [mm]	F [mm]	S [mm]	R [mm]	m [kg]
60	20	14M-60-S20	9	GG	3020	75,0	267,38	264,58	-	159,0	224,0	33,0	51,0	9,0	12,59
	37	14M-60-S37	7	GG	3020	75,0	267,38	264,58	-	159,0	224,0	51,0	51,0	0,0	14,23
	68	14M-60-S68	6	GG	3525	100,0	267,38	264,58	-	-	224,0	84,0	65,0	9,5	24,28
	90	14M-60-S90	6	GG	3525	100,0	267,38	264,58	-	-	224,0	106,0	66,0	20,0	26,53
	125	14M-60-S125	6	GG	4030	115,0	267,38	264,58	-	-	224,0	141,0	76,0	32,5	30,92
64	20	14M-64-S20	9	GG	3020	75,0	285,21	282,41	-	159,0	242,0	33,0	51,0	9,0	13,84
	37	14M-64-S37	7	GG	3020	75,0	285,21	282,41	-	159,0	242,0	51,0	51,0	0,0	15,58
	68	14M-64-S68	6	GG	3525	100,0	285,21	282,41	-	-	242,0	84,0	65,0	9,5	27,86
	90	14M-64-S90	6	GG	3525	100,0	285,21	282,41	-	-	242,0	106,0	66,0	20,0	30,30
	125	14M-64-S125	6	GG	4030	115,0	285,21	282,41	-	-	242,0	141,0	76,0	32,5	35,34
72	20	14M-72-S20	9	GG	3020	75,0	320,86	318,06	-	159,0	278,0	33,0	51,0	9,0	15,51
	37	14M-72-S37	7	GG	3020	75,0	320,86	318,06	-	159,0	278,0	51,0	51,0	0,0	17,24
	68	14M-72-S68	7	GG	3525	100,0	320,86	318,06	-	178,0	278,0	84,0	65,0	9,5	25,74
	90	14M-72-S90	7	GG	3525	100,0	320,86	318,06	-	178,0	278,0	106,0	66,0	20,0	26,36
	125	14M-72-S125	7	GG	4030	115,0	320,86	318,06	-	215,0	278,0	141,0	76,0	32,5	37,71
80	20	14M-80-S20	9	GG	3020	75,0	356,51	353,71	-	159,0	314,0	33,0	51,0	9,0	18,13
	37	14M-80-S37	7	GG	3020	75,0	356,51	353,71	-	159,0	314,0	51,0	51,0	0,0	20,32
	68	14M-80-S68	7	GG	3525	100,0	356,51	353,71	-	178,0	314,0	84,0	65,0	9,5	29,86
	90	14M-80-S90	7	GG	4030	115,0	356,51	353,71	-	215,0	314,0	106,0	76,0	15,0	35,61
	125	14M-80-S125	7	GG	4030	115,0	356,51	353,71	-	215,0	314,0	141,0	76,0	32,5	42,02
90	20	14M-90-S20	10	GG	3020	75,0	401,07	398,27	-	159,0	360,0	33,0	51,0	9,0	19,47
	37	14M-90-S37	8	GG	3020	75,0	401,07	398,27	-	159,0	360,0	51,0	51,0	0,0	29,85
	68	14M-90-S68	8	GG	3525	100,0	401,07	398,27	-	178,0	360,0	84,0	65,0	9,5	31,24
	90	14M-90-S90	7	GG	4030	115,0	401,07	398,27	-	215,0	360,0	106,0	76,0	15,0	41,90
	125	14M-90-S125	7	GG	4030	115,0	401,07	398,27	-	215,0	360,0	141,0	76,0	32,5	51,29
112	20	14M-112-S20	10	GG	3020	75,0	499,11	496,31	-	159,0	456,0	33,0	51,0	9,0	24,25
	37	14M-112-S37	8	GG	3020	75,0	499,11	496,31	-	159,0	456,0	51,0	51,0	0,0	27,43
	68	14M-112-S68	8	GG	3525	100,0	499,11	496,31	-	178,0	456,0	84,0	65,0	9,5	39,25
	90	14M--S11290	8	GG	4535	125,0	499,11	496,31	-	215,0	456,0	106,0	90,0	8,0	70,89
	125	14M-112-S125	8	GG	4535	125,0	499,11	496,31	-	215,0	581,0	141,0	89,0	26,0	65,64
140	20	14M-140-S20	10	GG	3020	75,0	623,89	621,09	-	159,0	581,0	33,0	51,0	9,0	20,96
	37	14M-140-S37	10	GG	3525	100,0	623,89	621,09	-	206,0	581,0	51,0	65,0	7,0	33,55
	68	14M-140-S68	8	GG	3525	100,0	623,89	621,09	-	206,0	581,0	84,0	65,0	9,5	40,87
	90	14M-140-S90	8	GG	4535	125,0	623,89	621,09	-	215,0	581,0	106,0	90,0	8,0	74,56
	125	14M-140-S125	8	GG	4535	125,0	623,89	621,09	-	215,0	581,0	141,0	89,0	26,0	67,90
168	37	14M-168-S37	10	GG	3525	100,0	748,66	745,87	-	206,0	706,0	51,0	65,0	7,0	64,50
	68	14M-168-S68	8	GG	3525	100,0	748,66	745,87	-	206,0	706,0	84,0	65,0	9,5	73,30
	90	14M-168-S90	8	GG	5040	130*	748,66	745,87	-	267,0	708,0	106,0	102,0	2,0	109,24
	125	14M-168-S125	8	GG	5040	125,0	748,66	745,87	-	267,0	706,0	141,0	102,0	19,5	120,66
192	37	14M-192-S37	10	GG	4030	115,0	855,61	852,82	-	215,0	812,0	51,0	76,0	12,5	83,82
	68	14M-192-S68	8	GG	4030	115,0	855,61	852,82	-	215,0	812,0	84,0	76,0	4,0	94,21
	90	14M-192-S90	8	GG	5040	130,0	855,61	852,82	-	267,0	812,0	106,0	102,0	2,0	126,05
	125	14M-192-S125	8	GG	5040	125,0	855,61	852,82	-	267,0	812,0	141,0	102,0	19,5	142,39

\* Materiál: ST = ocel, GG = litina / ST = steel, GG = iron cast