

Ridge top V-belts

2C, PU75A / PU80A white/transparent












Order No.	Profile dimension mm	Cross section cm ²	approx. weight kg/100m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)	
				m	ft	mm	inch	kg	lbs
FBSP85A17K2	17 x 19	2,0	24,4	30	100	160	6,4	48,0	105,6
FBSP85A22K2	22 x 25	3,5	42,3	30	100	200	8,0	84,0	184,8

approx. 80/84° Shore A


Recommended pretension: 3...6 %, **Coeff. of friction μ** : Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30

Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms	Belt made of 2 components enables combination of hardness and features.

Ridge top V-belts

2C, PU75A / PU80A white/transparent, reinforced Aramid












Order No.	Profile dimension mm	Cross section cm ²	approx. weight kg/100m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)	
				m	ft	mm	inch	kg	lbs
FBZSP85A17K2	17 x 19	2,0	24,4	30	100	170	6,8	48,0	105,6
FBZSP85A22K2	22 x 25	3,5	42,3	30	100	210	8,4	84,0	184,8

approx. 80/84° Shore A

Recommended pretension: 0,5...2 %, **Coeff. of friction μ**: Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30

Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms	Belt made of 2 components enables combination of hardness and features.