


Ridge top V-belts

PU95A beige












Order No.	Profile dimension mm	Cross section cm ²	approx. weight kg/100m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)	
				m	ft	mm	inch	kg	lbs
FBAM17X19BG	17 x 19	1,95	23,6	30	100	200	8	97,5	214,5
FBAM22X25BG	22 x 25	3,26	39,1	30	100	250	10	163,0	358,6

approx. 95° Shore A


Recommended pretension: 3...5 %, **Coeff. of friction μ** : Steel: approx. 0,45 | PE: approx. 0,25 | HDPE: approx. 0,20

Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for microorganisms	Belt made of 2 components enables combination of hardness and features.

Ridge top V-belts

PU95A beige












Form 2

approx. 95° Shore A

Order No.	Profile dimension mm	Cross section cm ²	approx. weight kg/100m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)	
				m	ft	mm	inch	kg	lbs
FBBM17X19BG	17 x 19	2,13	25,6	30	100	210	8,4	106,5	234,3
FBBM22X25BG	22 x 25	3,65	43,8	30	100	260	10,4	182,5	401,5

Recommended pretension: 3...5 %, **Coeff. of friction μ** : Steel: approx. 0,45 | PE: approx. 0,25 | HDPE: approx. 0,20

Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for microorganisms	Belt made of 2 components enables combination of hardness and features.