

Can Cables

PU95A red smooth, reinforced Aramid












approx. 95° Shore A

Order No.	Diameter ∅		Cross section cm ²	approx. weight kg/100m	Standard roll		Recommended Min. pulley ∅*		Fmax/belt (Standard)		Fmax/belt (Overlap)	
	mm	inch			m	ft	mm	inch	kg	lbs	kg	lbs
FBRN095RM	9,5	3/8	0,71	8,5	152	500	175	6,9	35,5	78,1	210	462
FBRN100RM	10,0	7/16	0,785	9,4	152	500	185	7,3	39,3	86,5	210	462
FBRN120RM	12,0	15/32	1,13	13,5	152	500	220	8,7	56,6	124,5	210	462
FBRN125RM	12,5	1/2	1,23	14,8	152	500	230	9,1	61,6	136	210	462

Recommended pretension 0,5...2 %, **Coeff. of friction μ**: Steel: approx. 0,40 | PE: approx. 0,25 | HDPE: approx. 0,20


*Overlap +30%; ★ Crimp sleeve connection / connection set and tool on page 109.

Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for microorganisms	Belt made of 2 components enables combination of hardness and features.

Can Cables

PU95A red slightly rough, reinforced Aramid












approx. 95° Shore A

Order No.	Diameter ∅		Cross section cm ²	approx. weight kg/100m	Standard roll		Recommended Min. pulley ∅*		Fmax/belt (Standard)		Fmax/belt (Overlap)	
	mm	inch			m	ft	mm	inch	kg	lbs	kg	lbs
FBRN095RMA	9,5	3/8	0,71	8,5	152	500	175	6,9	35,5	78,1	210	462

Recommended pretension 0,5...2 %, **Coeff. of friction μ**: Steel: approx. 0,40 | PE: approx. 0,25 | HDPE: approx. 0,20

*Overlap +30%; ★ Crimp sleeve connection / connection set and tool on page 109.

Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms	Belt made of 2 components enables combination of hardness and features.